

B75DM VER:1.0 规格表



B75DM VER:1.0 正面图



B75DM VER1.0 IO 图



B75DM VER1.0 侧面图

Product model	B75DM VER:1.0
processor	Supports LGA1155 architecture 2th/3th Intel® Celeron/Pentium/Core™ i3/i5/i7 processors
chipset	Intel B75 high-speed chipset
memory	2 * DDR3 DIMM slots for dual-channel 1066mhz memory, 1333mhz memory, and 1600MHz memory, up to 16GB
reveal	Integrated Intel® HD Graphics controller with 1*VGA port and 1*HD OUTPUT1.4 port Supports single display mode, dual display mode, and extended mode
network	1* Intel I211AT Gigabit network adapter, supporting network wake up and PXE functions 1* Intel I219V Gigabit network adapter, supporting network wake up and PXE functions
store	5* SATA 2.0 hard disk interface,SATA interface transmission speed up to 3Gbps 1* MSATA SSD interface, transmission speed up to 6Gbps
Audio frequency	Integrated ALC892 high fidelity audio controller, support Mic, Line out
Expansion slot	1* PCIE x16 1* PCIE x4 1* PCIE x1 4* PCI 1* Mini-PCIE, WiFi support (optional TPM-4COM board, can expand 4 serial ports)
I/O ports on the backplane	1* PS/2 keyboard and mouse interface 1 x VGA display port 1* HD OUTPUT display interface 2* RS232 serial port, COM1/2 supports 5V/12V power function, COM1/2 supports RS485/422 function



	2* USB 2.0 port
	4* USB 3.0 interface
	2* RJ-45 Gigabit network interface
	1* Line out interface (green), 1* MIC interface (red)
Built-in I/O interface	4*RS232 serial port
	1*JVGA1 interface, 1*12pin row pin, same signal as external VGA
	1* PS/2 keyboard and mouse interface 1*6pin row pins
	1*LPT print port 2*13pin row pin 2.54mm
	1* front audio interface 2*5pin row pins
	4* USB 2.0 port 2*5Pin row pins
	1*USB2.0 port USB-TYPE A
	1* Front panel function buttons and indicator ports 2*5pin row pins
	1*24pin ATX power input interface
	2*4pin ATX power input interface
	1*AC Power-on automatic power-on function 1*3pin row
Fan interface	2*4pin CPU intelligent fan interface, 2*4pin system intelligent fan interface
GPIO	Supports four input/output GPIO functions
BIOS	64Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 7/Linux
Power supply type	24Pin ATX power supply
Operating temperature	-10°C to 60°C
Storage temperature	-20°C to 70°C
Working	5 ~ 90% relative humidity, no condensation



humidity	
dimension	305mm * 220mm (ATX)

订购信息：

No.	Model	Processor	Southbridge	Memory	VGA	HD OUTPUT	LAN	USB	COM	RS485/RS422	Power
1	B75DM VER:1.0	LGA1155	B75	2*DDR3	1	1	1*I211AT 1*I219V	11	6	COM1/COM2	ATX