



研域  
YENTEK

## EPIC-E41\_J126L VER:1.1 Spec.



EPIC-E41\_J126L VER:1.1E Front View



EPIC-E41\_J126L VER:1.1E I/O View



EPIC-E41\_J126L VER:1.1E Lateral View



<b>Model No.</b>	EPIC-E41_J126L VER:1.1E
<b>Processor</b>	Onboard Intel®Celeron J4125 2.0GHz quad Core 4-thread processor, TDP 10W Compatible with Intel® Gemini Lake series CPU
<b>Chipset</b>	SOC
<b>Memory</b>	1* SODIMM slot, support single channel 2400MHz DDR4 memory, up to 8GB
<b>Display</b>	Integrate Intel® UHD Graphics 600 1*VGA,1*HDMI port,1*LVDS port
<b>Network</b>	2* RTL8111H Gigabit network card, support Wake on LAN, PXE function
<b>Storage</b>	1* 7pin SATA3.0 hard disk port, the transfer rate up to 3Gbps 1* MSATA slot, supports SSD solid state drive of Intel protocol, the transfer rate up to 6Gbps
<b>Audio</b>	Integrated ALC662 6 channel high-fidelity audio controller, supporting MIC, Line_out, power amplifier Support power amplifier 2Ω5W speaker
<b>Expansion Slot</b>	1* Mini-PCIE slot,support WIFI/4G module
<b>Rear I/O Port</b>	1* DC12V power interface, support 12V power input 1*VGA interface 1*HDMI interface 2*USB3.0 interface,1*USB2.0 interface 2* RJ45 Gigabit network interface 1* Line-out (green)
<b>Built in I/O Port</b>	1* DC power adaptor,1*4pin support 12V power input/output 1* JVGA interface 1*12pin (same signal as DB15) 1* LVDS interface 2*15pin, support dual channel 24bit 1* Screen brightness adjustment interface 1*6pin 4* USB2.0 interface, 2*5pin, 6* RS232 serial interface,COM2/3 support RS485/422 function 1* Hard disk power supply interface 1*4pin 1* Front audio interface 2*5pin 1* power amplifier interface 1*4pin 1* SIM card connector 1* Front panel switch button and indicator light interface 2*5Pin
<b>Fan Connector</b>	Fanless cooling, reserved 1*4pin CPU intelligent fan interface, 1*4pin system fan interface



<b>GPIO</b>	Support 4-in 4-out GPIO function
<b>BIOS</b>	64Mb Flash ROM
<b>Watchdog</b>	Support hardware reset function (L256, 0~255 seconds)
<b>Support OS</b>	Windows 10/Linux
<b>Power Type</b>	Adopt DC 12V power supply
<b>Working Temp.</b>	-10°C~60°C
<b>Storage Temp.</b>	-20°C~70°C
<b>Working Temp.</b>	5%-95% relative humidity, non-condensing
<b>Dimension</b>	148mm x 102mm

## Order Information:

No	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	RS485/422	Power
1	EPIC-E41_J126L VER:1.1E	J4125	2.0G	1* SODDR4	1	1	2ch*24BIT	/	2*8111H	7	6	COM2/3	DC12V